


STRONG-POINT™ Deck Screws

STRONG-POINT®

Attach wood to metal, and wood to wood with confidence, using **Professional-Grade** deck screws

Phillips Bugle Head Coarse Thread




Attaches Wood
to Wood

Lengths
1-1/4" - 3"

WAR Coated

WAR
Corrosion Protection - ACQ Compatible

Square Drive Bugle Head Coarse Thread




Attaches Wood
to Wood

Lengths
1-5/8" - 3-1/2"

WAR Coated

WAR
Corrosion Protection - ACQ Compatible

Star Drive Flat Head w/Nibs Coarse Thread




Attaches Wood
to Wood

Lengths
1-1/4" - 6"

WAR Coated

WAR
Corrosion Protection - ACQ Compatible

Phillips Flat Head Reamer w/Wings




Attaches Wood
to Metal

Lengths
2" - 4-3/4"

WAR Coated

WAR
Corrosion Protection - ACQ Compatible


305 Stainless Bugle Head Coarse Thread



Attaches Wood
to Wood

Lengths
1-1/4" - 3"


305 Stainless Flat Head w/Nibs Coarse Thread



Attaches Wood
to Wood

Lengths
1-1/4" - 4"


305 Stainless Trim Head Coarse Thread



Attaches Wood
to Wood

Lengths
1-5/8" - 3"

316 Stainless Flat Head w/Nibs Coarse Thread



Attaches Wood
to Wood

Lengths
2-1/2" - 3-1/2"

410 Stainless Flat Head Reamer w/Wings



Attaches Wood
to Metal

Lengths
2-1/2" - 3-1/4"



MUDGE
FASTENERS, INC.

3050 Palisades Dr.
Corona, CA 92880

951-270-1360 Phone
951-273-0110 Fax

www.mudgefasteners.com

Phillips Bugle Head, Coarse Thread, WAR Coated



- Meets ASTM A 510 for carbon steel manufacturing
- Meets ASTM B-117 for salt spray corrosion testing
- Designed to work with ACQ treated lumber
- Exceeds 1,000/hr. salt spray resistance

Material Application
Exterior wood screw for outdoor applications. Attaches wood to wood.



| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|-----------|--------------|----------|------|-------------|---------|-------------|---------|
| 6 x 1-1/4 | 614CW | 8M | 29 | 614CWV | 1,300 | 614CWI | 250 |
| 6 x 1-5/8 | 615CW | 5M | 22 | 615CWV | 1,000 | 615CWI | 200 |
| 6 x 2 | 620CW | 3.5M | 19 | 620CWV | 700 | 620CWI | 175 |
| 8 x 2-1/2 | 822CW | 2.5M | 22 | 822CWV | 400 | 822CWI | 100 |
| 8 x 3 | 830CW | 2M | 21 | 830CWV | 400 | 830CWI | 100 |

Square Drive Bugle Head, Coarse Thread, Type '17', WAR Coated




- Meets ASTM A 510 for carbon steel manufacturing
- Designed to work with ACQ treated lumber
- Exceeds 1,000/hr. salt spray resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application
Exterior wood screw for outdoor applications. Attaches wood to wood.



| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|------------|--------------|----------|------|-------------|---------|-------------|---------|
| 6 x 1-5/8 | XQ615W | 5M | 22 | XQ615WV | 1,000 | XQ615WI | 200 |
| 6 x 2 | XQ620W | 3.5M | 19 | XQ620WV | 700 | XQ620WI | 175 |
| 8 x 2-1/2 | XQ822W | 2.5M | 22 | XQ822WV | 400 | XQ822WI | 100 |
| 8 x 3 | XQ830W | 2M | 21 | XQ830WV | 400 | XQ830WI | 100 |
| 10 x 3-1/2 | XQ1031W | 1M | 18 | XQ1031WV | 250 | XQ1031WI | 50 |

Star Drive Flat Head w/Nibs, Coarse Thread, Type '17', WAR Coated



- Star drive prevents cam out and stripping for improved driveability
- Designed to work with ACQ treated lumber
- Exceeds 1,000/hr. salt spray resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application
Exterior wood screw for outdoor applications. Attaches wood to wood.




| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|------------|--------------|----------|------|-------------|---------|-------------|---------|
| 8 x 1-1/4 | XT814W | 8M | 38 | XT814WV | 1,000 | XT814WI | 200 |
| 8 x 1-5/8 | XT815W | 5M | 30 | XT815WV | 800 | XT815WI | 150 |
| 8 x 2 | XT820W | 3.5M | 25 | XT820WV | 700 | XT820WI | 140 |
| 9 x 2-1/2 | XT922W | 2.5M | 26 | XT922WV | 400 | XT922WI | 100 |
| 9 x 3 | XT930W | 2M | 24 | XT930WV | 400 | XT930WI | 100 |
| 10 x 3-1/2 | XT1031W | 1M | 17 | XT1031WV | 250 | XT1031WI | 50 |
| 10 x 4 | XT1040W | .8M | 16 | XT1040WV | 250 | XT1040WI | 50 |
| 10 x 5 | XT1050W | .5M | 13 | XT1050WV | 200 | XT1050WI | 40 |
| 10 x 6 | XT1060W | .5M | 15 | XT1060WV | 125 | N/A | N/A |

*Carton weights are approximate and may vary.

Note: 5lb. boxes sold 6 per case. 1lb. boxes sold 20 per case.

Phillips Flat Head Reamer w/Wings, WAR Coated

Material Application
Attaches wood to metal.



- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Exceeds 1,000/hrs. salt spray resistance
- For use in pressure treated lumber
- Wings ream hole in wood preventing “jacking action”
- Used for attaching lumber or headers to steel

WAR®

| Size | Pt | Bulk Part No | Bulk Qty | Lbs* | Drill Cap (in.) | Wood Range | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|----------------|----|--------------|----------|------|-----------------|---------------|-------------|---------|-------------|---------|
| 12-24 x 2 | 3 | R200W | 2M | 32 | .110 - .210 | 1/2" - 1-1/8" | R200WV | 300 | R200WI | 50 |
| 12-24 x 2-1/2 | 4 | R212W | 1.5M | 30 | .110 - .250 | 1/2" - 1-1/2" | R212WV | 250 | R212WI | 50 |
| 1/4-20 x 2-3/4 | 4 | R234W | 1M | 30 | .110 - .375 | 3/4" - 1-3/4" | R234WV | 165 | R234WI | 30 |
| 1/4-20 x 3-1/4 | 4 | R314W | 1M | 35 | .110 - .375 | 3/4" - 2-1/4" | R314WV | 150 | R314WI | 30 |
| 1/4-20 x 3-1/2 | 4 | R312W | .8M | 30 | .110 - .375 | 3/4" - 2-1/2" | R312WV | 130 | R312WI | 25 |
| 1/4-20 x 3-3/4 | 4 | R334W | .5M | 20 | .110 - .375 | 3/4" - 2-3/4" | R334WV | 125 | R334WI | 25 |
| 1/4-20 x 4-3/4 | 4 | R434W | .5M | 27 | .110 - .375 | 3/4" - 3-3/4" | R434WV | 100 | R434WI | 20 |

305 Stainless Steel Phillips Bugle Head, Coarse Thread

Material Application
Exterior wood screw for outdoor applications. Attaches wood to wood.



- For fencing, decks, patio furniture, spas
- High degree of corrosion resistance

| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|-----------|--------------|----------|------|-------------|---------|-------------|---------|
| 8 x 1-1/4 | 814CSS | 8M | 40 | 814CSSV | 1,000 | 814CSSI | 200 |
| 8 x 1-5/8 | 815CSS | 5M | 31 | 815CSSV | 750 | 815CSSI | 150 |
| 8 x 2 | 820CSS | 3.5M | 25 | 820CSSV | 500 | 820CSSI | 100 |
| 8 x 2-1/2 | 822CSS | 2.5M | 23 | 822CSSV | 400 | 822CSSI | 100 |
| 8 x 3 | 830CSS | 2M | 22 | 830CSSV | 400 | 830CSSI | 80 |

305 Stainless Steel Star Drive Flat Head w/Nibs, Coarse Thread, Type '17'

Material Application
Exterior wood screw for outdoor applications. Attaches wood to wood.



- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- High degree of corrosion resistance
- Nibs under head provide flush finish
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|------------|--------------|----------|------|-------------|---------|-------------|---------|
| 8 x 1-1/4 | XT814SS | 5M | 23 | XT814SSV | 1,000 | XT814SSI | 200 |
| 8 x 1-5/8 | XT815SS | 4M | 23 | XT815SSV | 800 | XT815SSI | 160 |
| 8 x 2 | XT820SS | 3M | 22 | XT820SSV | 700 | XT820SSI | 150 |
| 10 x 2-1/2 | XT1022SS | 2M | 24 | XT1022SSV | 400 | XT1022SSI | 80 |
| 10 x 3 | XT1030SS | 1.5M | 22 | XT1030SSV | 300 | XT1030SSI | 60 |
| 10 x 3-1/2 | XT1031SS | 1M | 17 | XT1031SSV | 250 | XT1031SSI | 50 |
| 12 x 4 | XT1240SS | 1M | 28 | XT1240SSV | 165 | XT1240SSI | 40 |

*Carton weights are approximate and may vary.

Note: 5lb. and 1lb. Stainless Steel boxes sold per case or individually.

305 Stainless Steel Square Drive Trim Head, Coarse Thread, Type '17'



- Superior penetration through a variety of woods
- High degree of corrosion resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for attaching trim and rails to decks or fences.

| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|-----------|--------------|----------|------|-------------|---------|-------------|---------|
| 7 x 1-5/8 | X1QSS | 5M | 29 | X1QSSV | 1,000 | X1QSSI | 200 |
| 7 x 2-1/4 | X2QSS | 3M | 23 | X2QSSV | 600 | X2QSSI | 125 |
| 7 x 3 | X3QSS | 2M | 21 | X3QSSV | 500 | X3QSSI | 100 |

305 Stainless Steel Star Drive Trim Head, Coarse Thread, Type '17'



- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- High degree of corrosion resistance
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for attaching trim and rails to decks or fences.

| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|-----------|--------------|----------|------|-------------|---------|-------------|---------|
| 7 x 1-5/8 | X1TSS | 5M | 29 | X1TSSV | 1,000 | X1TSSI | 200 |
| 7 x 2-1/4 | X2TSS | 3M | 23 | X2TSSV | 600 | X2TSSI | 125 |
| 7 x 3 | X3TSS | 2M | 21 | X3TSSV | 500 | X3TSSI | 100 |

316 Stainless Steel Star Drive Flat Head w/Nibs, Coarse Thread, Type '17' **NEW ITEM!**




- Star drive prevents cam out and stripping for improved driveability
- Superior penetration through a variety of woods
- Maximum degree of corrosion resistance
- Nibs under head provide flush finish
- Type '17' reduces wood splitting and eliminates the need for pre-drilling

Material Application

Exterior wood screw for outdoor applications. Attaches wood to wood.

| Size | Bulk Part No | Bulk Qty | Lbs* | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|------------|--------------|----------|------|-------------|---------|-------------|---------|
| 10 x 2-1/2 | XT1022MG | 2M | 25 | XT1022MGV | 400 | XT1022MGI | 80 |
| 10 x 3 | XT1030MG | 1.5M | 22 | XT1030MGV | 300 | XT1030MGI | 60 |
| 10 x 3-1/2 | XT1031MG | 1M | 17 | XT1031MGV | 250 | XT1031MGI | 50 |

410 Stainless Steel Star Drive Flat Head Reamer w/Wings, Strong-Shield Coated



- Meets ASTM C 1513 for cold-formed steel framing connections
- Meets F.I.P.-1000.7 for torsional strength & drill speed
- Meets SAE J78 for performance & dimensional specifications
- Rust/Acid Rain Protection
- ACQ Compatible
- Exceeds 1,000/hr. salt spray resistance

Material Application

Attaches wood to metal.



| Size | Pt | Bulk Part No | Bulk Qty | Lbs* | Drill Cap (in.) | Wood Range | 5lb Part No | 5lb Qty | 1lb Part No | 1lb Qty |
|----------------|----|--------------|----------|------|-----------------|---------------|-------------|---------|-------------|---------|
| 12-24 x 2-1/2 | 4 | 4RT212 | 1M | 21 | .110 - .375 | 1/2" - 1-1/2" | 4RT212V | 250 | 4RT212I | 50 |
| 1/4-20 x 2-3/4 | 4 | 4RT234 | .8M | 24 | .110 - .375 | 1/2" - 1-3/4" | 4RT234V | 160 | 4RT234I | 30 |
| 1/4-20 x 3-1/4 | 4 | 4RT314 | .5M | 17 | .110 - .375 | 3/4" - 2-1/4" | 4RT314V | 125 | 4RT314I | 25 |

*Carton weights are approximate and may vary.

Note: 5lb. and 1lb. Stainless Steel boxes sold per case or individually.